

COMPARISON GUIDE: TRAILER TRACKING



DEVICE NAME	PC-830	PS-345	PS-290	PS-955	PG-1C	PG-1S
Reporting Data	<p>Basic Option:</p> <ul style="list-style-type: none"> • Location • Backup Battery Device Status • Connection Status • Connection Time • Connection Voltage <p>Optional Add-ons:</p> <ul style="list-style-type: none"> • Temperature 	<p>Basic Option:</p> <ul style="list-style-type: none"> • Location • Battery Voltage • Backup Battery Device Status • Ignition Status • Runtime <p>Optional BLE Add-ons:</p> <ul style="list-style-type: none"> • Temperature • Humidity • Door • Tire Pressure • And More 	<p>Location Battery Level</p>	<p>Location Battery Level</p>	<p>Location Battery Status</p>	<p>Location Battery Status</p>
Default Reporting Intervals	<p>Moving: 1/Hr or 1/Min Option Not Moving: 1/Hr No Power: 1/Week</p>	<p>Moving: Every 1-2 Minutes Not Moving: Every 10 Minutes</p>	<p>1 or 2/Day Option</p>	<p>Moving: Start/Stop & Every 15 Min Not Moving: 1/Day</p>	<p>1 or 2/Day Option</p>	<p>1 or 2/Day Option</p>
Communication	<p>Cellular</p>	<p>Cellular</p>	<p>Cellular</p>	<p>Cellular</p>	<p>Satellite</p>	<p>Satellite</p>
Network/Connectivity	<p>AT&T, Verizon, & Others 4G LTE CAT M1</p>	<p>AT&T, Verizon, & Others 4G LTE CAT M1</p>	<p>AT&T, Verizon, & Others 4G LTE CAT M1</p>	<p>AT&T, Verizon, & Others 4G LTE CAT M1</p>	<p>Globalstar Satellite Network</p>	<p>Globalstar Satellite Network</p>
Estimated Battery Life	<p>Approx. 9 months</p>	<p>Up to 2 Weeks</p>	<p>Up to 5 Years</p>	<p>Up to 10 Years</p>	<p>Up to 1 Year</p>	<p>Up to 10 Years</p>

COMPARISON GUIDE: TRAILER TRACKING



DEVICE NAME	PC-830	PS-345	PS-290	PS-955	PG-1C	PG-1S
Battery	5300mAh Lithium-ion	Rechargeable 3.7V, Lithium-Ion 450mAh	19Ah Lithium Proprietary	10.8Ah Lithium Proprietary	Energizer Ultimate Lithium AAA	NiMH Proprietary
Field Replaceable Battery	No	No	Replaced by Pedigree Technician Only	No	Yes	No
OTA Updates	Yes	Yes	Yes	Yes	No	No
Ping on Demand	No	No	No	No	No	No
BLE Sensor Support	Yes	Yes	No	Yes	No	No
IP Rating	IP66	IP67	IP67	IP67	IP68	IP69K
Dimensions	4.5" x 3.2" x 1.6"	2.9" x 1.7" x 0.77"	2" x 3.6" x 1.8"	3.7" x 5.1" x 1.63"	3.25" x 1" x 2.7"	3.25" x 7" x 1.26"
Weight	20.45 oz	3.24 oz	5.9 oz	12.3 oz	3.6 oz	13.5 oz
Operating Temperature	-22F to +140F	-22F to +176F	-31 F to +167 F	-30 F to +185 F	-22 F to +140 F	-40 F to +185 F
Installation Options	3M Adhesive Tape or Screws	3M Adhesive Tape or Screws When Using Protective Mount	3M Adhesive Tape or Screws When Using Protective Mount	3M Adhesive Tape or Screws When Using Protective Mount	3M Adhesive Tape or Screws When Using Protective Mount	3M Adhesive Tape or Screws
Accessories	Wiring/Runtime Relay	Mounting Bracket for Under Dash Install	Metal Bracket	Metal Bracket, Wired Charger	Protective Bracket, External Cable for Runtime Monitoring	N/A