

COMPARISON GUIDE: ASSET TRACKING



DEVICE NAME	PS-290	PS-955	PG-1S	PG-1C
Reporting Data	Location Battery Level	Location Battery Level	Location Battery Status: Normal or Low	Location Battery Status: Normal or Low
Default Reporting Intervals	1x or 2x Per Day	1x Per Day and Start/Stop (Motion) & Every 15 min. When Moving	1x or 2x Per Day	1x or 2x Per Day
Communication	Cellular	Cellular	Satellite	Satellite
Network/ Connectivity	AT&T, Verizon, & Others 4G LTE CAT M1 & NB-IoT	AT&T, Verizon, & Others 4G LTE CAT M1 & NB-IoT	Globalstar Satellite Network	Globalstar Satellite Network
Estimated Battery Life	Up to 5 Years	Up to 10 Years	Up to 10 Years	Up to 2 Years
Battery	19Ah Lithium Proprietary	10.8Ah Lithium Proprietary	NiMH Proprietary	Energizer Ultimate Lithium AAA
Field Replaceable Battery	Replaced by Pedigree Technician Only	No	No	Yes

COMPARISON GUIDE: ASSET TRACKING



DEVICE NAME	PS-290	PS-955	PG-1S	PG-1C
OTA Updates	Yes	Yes	No	No
Ping on Demand	No	No	No	No
BLE Sensor Support	No	Yes	No	No
IP Rating	IP67	IP67	IP69K	IP68
Dimensions	2" x 3.6" x 1.8"	3.7" x 5.1" x 1.63"	3.25" x 7" x 1.26"	3.25" x 1" x 2.7"
Weight	5.9 oz	12.3 oz	13.5 oz	3.6 oz
Operating Temperature	-31 F to +167 F	-30 F to +185 F	-40 F to +185 F	-22 F to +140 F
Installation Options	3M Adhesive Tape or Screws When Using Protective Mount	3M Adhesive Tape or Screws When Using Protective Mount	3M Adhesive Tape or Screws	3M Adhesive Tape or Screws When Using Protective Mount
Accessories	Metal Bracket	Metal Bracket, Wired Charger	N/A	Protective Bracket, External Cable for Runtime Monitoring